

1. A leak detection instrument for monitoring gas leakage from a device, comprising:
 - a. an instrument housing;
 - b. a gas sensor supported relative to said instrument housing and operative upon exposure to a selected gas to generate a corresponding gas detection input signal;
 - c. an acoustic emissions (AE) sensor supported relative to said instrument housing and operative upon exposure to sound attendant with leakage of the selected gas to generate a corresponding sound detection input signal;
 - d. processing circuitry for receiving said gas detection input signal and said sound detection input signal and for producing at least one output signal in response thereto; and
 - e. an output device for producing perceptible output in response to said output signal.
2. A leak detection instrument according to claim 1 wherein said gas sensor is a chemical properties leak detector (CPLD).
3. A leak detection instrument detector according to claim 1 wherein said gas sensor is selected from a group consisting of a chemical properties leak detector (CPLD), a thermal conductivity detector (TCD), a photo-ionization detector (PID), a laser interferometer (LID), a corona discharge detector (CDD), a microelectromechanical (MEMS) based detector, a chemical resistor sensor (CRS), and a surface acoustic wave (SAW) detector .

4. A leak detection instrument according to claim 1 including a gas pump disposed within said instrument housing and operative upon actuation to draw the selected gas toward said gas sensor.
5. A leak detection instrument according to claim 4 wherein said AE sensor is supported relative to said instrument housing by an AE sensor mounting assembly.
6. A leak detection instrument according to claim 1 wherein said AE sensor is supported relative to said instrument housing by an AE sensor mounting assembly.
7. A leak detection instrument according to claim 5 wherein said AE sensor mounting assembly includes an elongated tubular extension having a proximal end removably attached to said instrument housing and extending from said proximal end to terminate at a distal end, and including an AE sensor housing disposed on said distal end.
8. A leak detection instrument according to claim 7 wherein said gas sensor is disposed within said instrument housing upstream of said pump, and wherein said tubular extension is a flexible member defining an airflow passageway between said AE sensor and said gas sensor.
9. A leak detection instrument according to claim 8 including a filter interposed between said AE sensor and said gas sensor.
10. A leak detection instrument according to claim 9 including a vacuum switch operative to monitor said filter and to produce a blocked filter indicator (BFI) signal for processing by said processing circuitry when said filter becomes contaminated and its efficacy reduced.

11. A leak detection instrument according to claim 8 wherein said pump is operative upon actuation to draw the target gas from an upstream end of said AE sensor mounting assembly, in a downstream direction along the airflow passageway, and toward said gas sensor.
12. A leak detection instrument according to claim 7 wherein said AE sensor is a micro phonic element supported within an interior of said AE sensor housing in electrical communication with said processing circuitry.
13. A leak detection instrument according to claim 12 including a plurality of LEDs supported within said AE sensor housing in electrical communication with said processing circuitry.
14. A leak detection instrument according to claim 13 wherein said AE sensor and said LEDs are mounted on a common circuit board.
15. A leak detection instrument according to claim 1 wherein said processing circuitry is operative to parallel process said gas detection input signal and said sound detection input signal.
16. A leak detection instrument according to claim 1 wherein said processing circuitry includes at least one processing component selected from a group consisting of a microprocessor, a microcontroller and a digital signal processor (DSP).
17. An acoustic emissions (AE) sensor mounting assembly adapted for connection to a scientific instrument that includes an instrument housing, processing circuitry for receiving an input sound detection signal and producing an output signal in response thereto, and an output device for generating perceptible output in response to the output signal, said AE sensor mounting assembly comprising:

- a. an elongated mounting member adapted to releaseably connect to the instrument housing, said elongated mounting member formed to include a gas flow passageway between respective ends thereof;
 - b. an AE sensor housing supported by said mounting member; and
 - c. an AE sensor disposed within said AE sensor housing and adapted to be placed in electrical communication with said processing circuitry, said AE sensor operative upon exposure to sound attendant with gas leakage from a device to generate the input sound detection signal for processing.
18. An AE sensor mounting assembly according to claim 17 wherein said elongated mounting member is a flexible tube having a proximal end releaseably connected to the instrument housing and extending from said proximal end to terminate at a distal end, said AE sensor housing supported on said distal end.
19. An AE sensor mounting assembly according to claim 17 wherein said AE sensor housing is releaseably connected to said mounting member.
20. An AE sensor mounting assembly according to claim 17 wherein said mounting member is a tubular extension and wherein said AE sensor housing includes a through bore in communication with the gas flow passageway of said mounting member.
21. An AE sensor mounting assembly according to claim 20 wherein said AE sensor housing includes a pair of bored end caps joined together to substantially surround an AE sensor housing interior.
22. An AE sensor mounting assembly according to claim 21 wherein a downstream one of said end caps is removably attached to said mounting

member, and wherein an upstream one of said end caps receives said AE sensor.

23. An AE sensor mounting assembly according to claim 21 wherein said AE sensor is a micro phonic element mounted on a circuit board that is supported within the AE sensor housing interior.
24. An AE sensor mounting assembly according to claim 23 including a plurality of ultraviolet LEDs mounted on said circuit board, said ultraviolet LEDs operative upon emission of ultraviolet light to cause an appropriately dyed target gas, or its residue, in a vicinity of said AE sensor housing to fluoresce.
25. An AE sensor mounting assembly according to claim 24 including at least one photo detector mounted on said circuit board and adapted to be placed in electrical communication with said processing circuitry, said photo detector being responsive to fluorescent light caused by said emission of ultraviolet light to generate a photo detection signal for processing.
26. An AE sensor mounting assembly according to claim 24 wherein said micro phonic element and said ultraviolet LEDs are mounted on a first surface of said circuit board and project forwardly in an upstream direction, and wherein an upstream one of said end caps includes a central bore that is directionally aligned with said micro phonic element, and a plurality of radially offset bores each axially aligned with a respective one of said ultraviolet LEDs, and including at least one visible LED mounted on said circuit board for emitting visible light upon emission of ultraviolet light from

said ultraviolet LEDs, thereby to indicate an on state for the ultraviolet LEDs.

27. An AE sensor mounting assembly according to claim 26 including a plurality of visible LEDs mounted on an opposite second surface of said circuit board and adapted to be placed in electrical communication with said processing circuitry, said visible LEDs operative upon emission of visible light to illuminate an area in a vicinity of said AE sensor housing.
28. An AE sensor mounting assembly according to claim 27 wherein said LEDs are equiangularly distributed about said micro phonic element.
29. An AE sensor mounting assembly according to claim 24 including a plurality of visible LEDs mounted on said circuit board and adapted to be placed in electrical communication with said processing circuitry, said visible LEDs operative upon emission of visible light to illuminate an area in a vicinity of said AE sensor housing.
30. An AE sensor mounting assembly according to claim 29 including a light transmissive annular ring sandwiched between said end caps in radial alignment with said visible LEDs.
31. In a leak detection instrument having an instrument housing, an acoustic emissions (AE) sensor supported relative to said instrument housing that is operative upon exposure to sound attendant with leakage from a device to produce a corresponding sound detection input signal, AE sensor processing circuitry disposed within said instrument housing for receiving the sound detection input signal and producing an AE sensor output signal in response thereto, and output circuitry for generating associated AE

sensor perceptible output in response to said AE sensor output signal, the improvement comprising:

- a. a gas sensor supported relative to the instrument housing, said gas sensor operative upon exposure to a selected gas to generate a corresponding gas detection input signal;
 - b. a pump supported relative to the instrument housing and operative upon actuation to draw air past said gas sensor; and
 - c. gas sensor processing circuitry in electrical communication with said gas sensor, said gas sensor processing circuitry operative in response to said gas detection input signal to generate a corresponding gas detection output signal.
32. The improvement according to claim 31 wherein each of the gas sensor and the pump are supported within the instrument housing.
33. The improvement according to claim 31 wherein said output circuitry is operative in response to said gas detection output signal to generate associated gas sensor perceptible output in response thereto.
34. The improvement according to claim 31 wherein said gas sensor is selected from a group consisting of a chemical properties leak detector (CPLD), a thermal conductivity detector (TCD), a photo-ionization detector (PID), a laser interferometer (LID), a corona discharge detector (CDD), a microelectromechanical (MEMS) based detector, a Chemical Resistor Sensor (CRS), and a surface acoustic wave (SAW) sensor.
35. In a leak detection instrument that includes an instrument housing, a gas sensor supported relative to said instrument housing that is operative upon exposure to a selected gas to generate a corresponding gas detection

input signal, a pump operative upon actuation to draw air past said gas sensor, and output circuitry for displaying associated gas sensor perceptible output in response to said gas detection input signal, the improvement comprising:

- a. an acoustic emissions (AE) sensor supported relative to the instrument housing and operative upon exposure to sound attendant with leakage of the selected gas to generate a corresponding sound detection input signal; and
 - b. AE sensor processing circuitry in electrical communication with said AE sensor, said AE sensor processing circuitry operative in response to said sound detection input signal to generate a corresponding sound detection output signal.
36. The improvement according to claim 35 wherein said AE sensor is supported externally of the instrument housing.
37. The improvement according to claim 35 wherein said output circuitry is operative in response to said sound detection output signal to generate associated AE sensor perceptible output in response thereto.
38. The improvement according to claim 35 wherein said AE sensor is a micro phonic element operative upon exposure to sound attendant with leakage of the selected gas to generate said sound detection input signal.
39. A method of monitoring a device to ascertain leakage of a target gas there from, comprising:
- a. providing a gas sensor that is operative upon exposure to the target gas to generate a corresponding gas detection input signal;

- b. providing an AE sensor that is operative upon exposure to airborne sound emanating from the device that is attendant with leakage of the target gas to generate a corresponding sound detection input signal;
 - c. exposing said gas sensor to the target gas whereby said gas sensor generates said gas detection input signal;
 - d. exposing said AE sensor to the airborne sound whereby said AE sensor generates said sound detection input signal;
 - e. processing said gas detection input signal and said sound detection input signal to produce at least one output signal in response thereto; and
 - f. displaying perceptible output in response to said output signal.
40. A method according to claim 39 whereby said sound detection input signal and said gas detection input signal are parallel processed.
41. A method according to claim 39 comprising creating a vacuum to draw the target gas along a gas flow passageway from an upstream location that is in a vicinity of a suspected leak towards a downstream location whereby the target gas encounters said gas sensor.
42. A method according to claim 41 including visibly illuminating an area in a vicinity of said upstream location.
43. A method according to claim 41 including illuminating an area in a vicinity of said upstream location with ultraviolet light, thereby to cause the target gas or its residue to fluoresce.
44. A method according to claim 39 including passing the target gas through a hydrophilic filter that interposed between said gas sensor and said AE sensor.

45. A method according to claim 44 including monitoring said hydrophilic filter in order to produce a blocked filter indication (BFI) signal for processing if efficacy of said filter is reduced below a selected threshold.
46. A method according to claim 39 whereby said gas detection input signal and said sound detection input signal are processed by at least one processing component selected from a group consisting of a microprocessor, a microcontroller and a digital signal processor (DSP).